

C Programming: Preparations

Obviously we need a text editor (some may want to call it code editor, to be more specific) to write code, a C compiler to compile the code and a linker to create the executable. What is most commonly used would probably be an Integrated Development Environment (IDE) which combines all of them into a single environment which is mainly the editor - the compiler and linker are just menu items or buttons somewhere within.

It is advisable to manage your source file in proper folder/path hierarchy. One thing about naming files and paths is NEVER use a whitespace character (' ') in them, no matter what Windows says about them not being a problem (Apparently, even Windows have ditched 'My Documents').

Code Editing

The source file is just a text file - so, you can actually use any text editor. On Windows platform, you can in fact use notepad or even the console-based `edit` (relic from DOS era) to write your code. The downside of using these editors are they lack syntax-highlighting which is very useful to start learning programming by helping you spot keyword/structure-related syntax errors early on. There are a lot of free code editors (text editor specifically for programming purpose that provides syntax highlighting) - a recommended editor is [Geany](#).

On Linux, IDEs are also available but many veteran programmers simply use Linux text editors which naturally supports syntax highlighting. Among the popular editors are Emacs and Vim. On popular distributions like Ubuntu, the supplied GUI-based editor (GNOME editor a.k.a. `gedit`, which is available on all distributions that use GNOME desktop) should be sufficient. On KDE desktop, `kwrite` or `kate` does the job pretty well.

Compiling (and Linking)

The instructions in this section require you to use the terminal. If you are using an IDE, just look for a menu item or button that says compile or build or make or something similar (they actually do the same thing as what is mentioned here).

If you have a single source file `this.c` this process can be done in a single step:

```
gcc this.c
```

By default, the `gcc` (GNU Compiler Collection instead of GNU C Compiler) compiler will create an executable called `a.out`. If you want to specify a name (e.g. `this`) you can use the `-o` parameter:

```
gcc -o this this.c
```

It does not need be similar to the name of your source file:

```
gcc -o what_the this.c
```

Note that both compiling and linking can be done in this single command. They are actually separate processes and most of the time, it is very useful to execute them in separate stages especially when managing a software with multiple source files.

Managing a Project

If you are using a full-fledged IDE, you will find everything but the kitchen sink available (sometimes a sink can also be found 😬). One of the things that make an IDE seems to work better is having a project management flow, i.e. keeping tracks of source files required to build the project, which compiler to use, etc. For an old school developer, using a makefile (requires make tool) makes more sense. This is what I am going to introduce here.

Like other configuration files in Unix/Linux systems, writing a makefile (which is also a simple text file) is relatively easy. Any strings following the '#' character are treated as comments. A simple example of a makefile that can be used to compile a C program from a single 'single.c' source file is shown below.

Note: This is based on GNU make utility. There are other variation(s) such as the BSD make.

makefile

```
# makefile to compile a c program
single: single.c
    gcc -o single single.c
```

I will explain the syntax after the next example. Take note that there should be a single hard tab before the gcc command. The given example however is not very convenient because I have to change a lot of things (three words at least in the example) if I decided to change file or project name. The example below gives us a more generic makefile.

makefile

```
# makefile to compile a c program
PROJECT = single
SOURCE = $(PROJECT).c
CC = gcc
$(PROJECT): $(SOURCE)
    $(CC) -o $(PROJECT) $(SOURCE)
```

The two common things that we do in a makefile is to define build rules and to define variables. The lines that contains a '=' is usually a variable definition. Any environment variable is imported into our make environment. A rule is defined by specifying a target that is done by specifying a label (or target object name) followed by a ':' character. In our example, the target is \$(PROJECT) - which is a variable and expands to single. Anything that comes after ':' will be considered as a prerequisite. If a target is older than any of its prerequisites, it will be rebuilt by make tool. The build process is defined by the

lines following the target (there can be more than 1 line). Notice that the **MUST BE** a hard tab character at the beginning of a process line.

Imagine now that you have a hundred source files. Using the above rule, changing one source file will cause all the other source files to be recompiled again. This is not very efficient. Thus, if you remember your introductory lecture for computer programming, an executable is built by combining object files and linking them to the respective libraries. Object files (*.o or *.obj) can be built independently. So, to have that, we alter our makefile to accommodate this.

makefile

```
# makefile to compile a c program
PROJECT = single
OBJECTS = $(PROJECT).o
CC = gcc
CFLAGS =
LDFLAGS =
$(PROJECT): $(OBJECTS)
    $(CC) $(CFLAGS) -o $@ $+ $(LDFLAGS)
%.o: %.c
    $(CC) $(CFLAGS) -c $<
```

There are a few new things here. Special variables like \$@, \$+ and \$< are now used. To know what they mean, you may refer to the note at the end of this section. The prerequisites are now object files that need to be built as well. In order to build these, make will refer to the second rule `%.o: %.c` - which says that any object files (*.o) need to be built depends on a source C file (*.c) that will be built using gcc with a `-c` parameter (compile only).

One thing you should know is make will use the first matching rule that it finds. So, if you have some object files that depend on both source (*.c) and header (*.h) files, you need to create the rule `%.o: %.c %.h` before the rule given above.

The given information so far about makefiles should be sufficient for basic projects. You will learn, in time, of more advanced ways to specify rules that will show you how the make tool can be a very powerful build management tool.

Some notes on special make variables:

```
# $@ ==> target file
# $? ==> changed dependents
# $* ==> shared target/dependent prefix
# $< ==> first dependent
# $^ ==> all dependents, duplicates omitted
# $+ ==> all dependents, order retained
```

Last update:

2026/08/11 learn:programming_c_00prep https://www.azman.my1matrix.cc/doku.php?id=learn:programming_c_00prep&rev=1786441214
09:40

From:

<https://www.azman.my1matrix.cc/> - Azman @MY1

Permanent link:

https://www.azman.my1matrix.cc/doku.php?id=learn:programming_c_00prep&rev=1786441214

Last update: **2026/08/11 09:40**

