

Slackware System

Useful system level notes.

Listing Packages

Simply list files in /var/log/packages (path is actually a link to /var/lib/pkgtools/packages/).

```
$ ls -l /var/log/packages/
```

List full package name (with version) only

```
$ for that in $(ls /var/log/packages/) ; do echo $that ; done | sort
```

List installed package name only

```
$ list=$(ls /var/log/packages/) ; for that in $list ; do that=${that%-*} ;  
that=${that%-*} ; that=${that%-*} ; echo $that ; done
```

Find installed packages that are not in Slackware tree

```
$ slackfull=slackware64-15.0 ; slacktree=/home/share/slackware/$slackfull ;  
for pkg in $(ls /var/log/packages/) ; do  
    pkgf=$(find $slacktree/ -name "${pkg}.txz") ;  
    [ -f "$pkgf" ] && continue ;  
    echo "*** Package '$pkg' is alien!" ;  
done
```

This can also be done using slackview script (in mylshell repo)

```
$ slackview find --alien
```

View information on specific package

```
$ slackview find [pkg_name]
```

To list all official packages without DE

```
$ for pack in a d k l n ap t tcl x xap ; do  
    slackview file --name pkgs.txt --insert --pack $pack ;  
done
```

To list currently installed packages (e.g. to be used in myllive)

```
$ slackview file --name pkgs.txt --insert --installed
```

To sort packages in *pkgs.txt* based on software sets

```
$ slackview file --name pkgs.txt --sort
```

To remove packages in *dups.txt* that is/are found in *pkgs.txt*

```
$ slackview file --name pkgs.txt --dups dups.txt
```

Building Custom Kernel

- run shell script ([getlinux](#))
- select version, download source
- extract at /usr/src/ (e.g. linux-4.4.199)
- copy a config from /boot

```
# cp /boot/config-generic? > .config
```

- use that config

```
# make oldconfig
```

- configure build

```
# make menuconfig
```

- build the kernel

```
# make -j4 bzImage
```

- build/install modules

```
# make -j4 modules && make modules_install
```

- `modules_install` requires root, obviously!

- copy (as root) kernel

```
cp arch/x86/boot/bzImage /boot/vmlinuz-generic-4.14.12
cp System.map /boot/System.map-generic-4.14.12
cp .config /boot/config-generic-4.14.12
```

- generate initrd if using generic

```
mkinitrd -c -k 4.14.12 -f ext4 -r /dev/sda3 -m ext4 -u -o
/boot/initrd.gz
```

- a useful initrd generator script IS available
- run `/usr/share/mkinitrd/mkinitrd_command_generator.sh`
- then run the generated/recommended command
- checkout the `-P` option if required

From:
<https://www.azman.my1matrix.cc/> - **Azman @MY1**

Permanent link:
https://www.azman.my1matrix.cc/doku.php?id=linux:slack_4system&rev=1784516806

Last update: **2026/07/20 03:06**

