

Scripting Stuff

My personal 'collection' of short scripts (mostly Linux/Unix shell) that I may need to refer in the future...

Fix Missing Leading Zero

Issue when creating CSV from spreadsheet program (e.g. Libreoffice Calc). The number string in column 3 of each line needs to be exactly 12 and the first line is a header line.

```
file=file.txt ; \  
( head -n 1 $file ; \  
tail -n +2 $file | \  
while read line ; do \  
line=${line// ,/,} ; \  
test=$(echo $line|cut -d',' -f3) ; \  
temp=$test ; \  
while [ ${#test} -lt 12 ] ; do \  
test="0$test" ; \  
done ; \  
line=${line//$temp/$test} ; \  
echo "$line" ; \  
done )
```

A script:

[check_nrid.sh](#)

```
#!/bin/bash  
  
# check_nrid.sh  
# - filters invalid nric in student list csv file for unidata  
# - assume input is list.csv  
# - run 'bash check_nric.sh list.csv >/dev/null' to check  
# - if nothing comes out, then the file is good  
# - run 'bash check_nrid.sh list.csv > list1.csv 2>/dev/null'  
# - will get fixed data in list1.csv  
  
check_nrid()  
{  
    local file loop line stid name nrid prog look prev  
    file=$1  
    [ ! -f $file ] && exit 0  
    loop=0  
    while read line ; do  
        if [ $loop -gt 0 ] ; then  
            stid=$(echo $line|cut -d',' -f1)
```

```

name=$(echo $line|cut -d',' -f2)
nrid=$(echo $line|cut -d',' -f3)
prog=$(echo $line|cut -d',' -f4)
look=0 prev=$nrid
while [ ${#nrid} -ne 12 ] ; do
    nrid="0$nrid"
    look=1
done
# trim prog
prog=${prog% }
line="$stid,$name,$nrid,$prog,,,"
if [ $look -ne 0 ] ; then
    echo "*** [$prev] $line" >&2
else
    echo "$line"
fi
fi
((loop++))
done < $file
}
check_nrid $@

```

Read line-by-line

```

while IFS="" read -r line || [ -n "$line" ] ; do
echo "> $line"
done <<< $(cat $file)

```

Ensure integer value

[get_integer.sh](#)

```

#!/bin/bash
get_integer()
{
    # use: get_integer <def_int> <var_int>
    local idf test temp
    idf=$1
    test=$2
    if [ ! -z $test ] ; then
        temp=$(echo "$test" | grep -E -v "^[0-9]*$")
        [ -z "$temp" ] && idf=$test
    fi
    echo -n "$idf"
}

```

```
[ "$(basename $0 sh)" = "get_integer" ] && get_integer $@
```

Some bash 1-liners

Find broken symbolic links in current path:

```
find $(pwd) -type l -exec test ! -e {} \; -print
```

From:

<https://www.azman.my1matrix.cc/> - Azman @MY1

Permanent link:

<https://www.azman.my1matrix.cc/doku.php?id=notes:scripting>

Last update: **2026/02/08 03:46**

